

рН/ОВП-метры CPR-411

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

WATERPROOF pH / ORP meter CPR-411

Used for simultaneous pH, mV (redox potential) and temperature measurements.

Characteristic features:

- Depending on the chosen electrode it may be used for measurements in clear or contaminated water in the field or in laboratory.
- The meter may be used for measurements in swimming pools.
- The model is equipped with BNC-50 connector for pH and redox electrodes and Chinch connector for the temperature probe.
- The pH and redox combination electrodes are isolated from each-other.



- Small size and low weight make working in the field easier.
- Large easy to read display enables simultaneous readout of one measuring function and temperature value or two measuring functions (pH and redox).
- Calibration of the pH electrode in 1, 2 or 3 points (pH: 4.00, 7.00, 9.00, or 4.00, 7.00, 10.00).
- Automatic buffer detection.
- Automatic temperature compensation.
- Readout of the electrode's slope and offset.

- Memory for 50 results.
- Possibility of automatic calculation of the redox potential result, received with the chloride/silver electrode, to the hydrogen electrode.
- Waterproof housing (IP-66) enables work in difficult conditions.
- Battery powered, for work in laboratory a power adapter may be used (optional equipment).
- Automatic switch-off function to save the battery.
- 24-month warranty for the meter, 12-month warranty for the electrode.
- Affordable price.



The offered electrode: **ERS-2** redox electrode for measurements in swimming pools

The standard set includes **CT2B-121** temperature sensor with **Pt-1000B** resistor, **ERS-2** redox electrode and **EPP-1** pH electrode for measurements in clear water, which should not be used in other types of liquid. Measurements in liquid with sediment should be made with use of **IJ44A** pH electrode, which enables measurements in various samples of both pure and contaminated liquids and semi-solids. Its unusual construction ("intermediate junction") protects the real junction (diaphragm) of the electrode against clogging, ensures stable measurements in these types of liquids or semi-liquid mass, in which other electrodes stop working quickly. When properly handled and maintained the electrode may be efficient for several years.

TECHNICAL DATA

Function	pH	Redox / mV	Temperature
Range	0.00 ÷ 14.00 pH	± 1999 mV	-50.0 ÷ 199.9 °C
Resolution	0.01pH	1 mV	0.1 °C
Accuracy (± 1 digit)	±0.01pH*	±1 mV*	±0.1 °C**
Input impedance	>10 ¹² Ω	>10 ¹² Ω	-
Temp. compensation	-5 ÷ 110 °C	-	-
Power supply	9 V battery, 12 V / 100 mA power adapter (option)		
Weight	210 g		
Dimensions (mm)	L=149, W=82, H=22		

*The accuracy of the meter only.

**The accuracy of the meter only. The total error includes the meters and probe's accuracy.

In the range 0 ÷ 100 °C the acceptable error of the probe with Pt-1000B resistor: ±0.8 °C, with Pt-1000A resistor: ±0.35 °C.

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93