

Измерители проводимости/солености СС-451

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

WATERPROOF CONDUCTIVITY / SALINITY / TDS METER CC-451

- **CC-451** measures conductivity, salinity, TDS and temperature. May be used in the field and laboratory.
- Colour, graphic touchscreen enables simultaneous readout of the conductivity / salinity / TDS and temperature value.
- Easy-in-use.
- Waterproof housing (IP-66) enables work in difficult conditions.
- Small size and low weight make working in the field easier.
- Measures conductivity in liquids up to 1000 mS/cm.
- 6 sub ranges switched automatically (autorange).
- Measures salinity with conversion to NaCl and KCl.
- Converts conductivity into salinity according to real characteristics and not a constant coefficient.
- TDS measurement, constant coefficient 0.5.
- 1-point calibration by entering the constant K of the cell or by determining it with use of a standard solution.
- Automatic temperature compensation.
- Constant α coefficient (the temperature compensation coefficient) – 2 %/°C.
- The reference temperature may be chosen between 25°C or 20°C.
- Memory of 200 results with time and date.
- Available 7 different languages: english, german, french, spanish, portuguese, italian, polish
- Calibration time reminding.



- **CC-451** in standard set is supplied with a **ECF-1** conductivity cell and a temperature sensor with a **Pt-1000B** resistor. The conductivity cell is designed for measurements both in clean water and liquids with deposits or fats. Its measuring range is up to 400 mS/cm. Plastic housing protects the cell from mechanical damage. It is possible to unscrew the measuring cell cover, what enables its easy cleaning. Metal electrodes may be cleaned with use of a brush in case of measurements in liquids with deposits.
- Powered by rechargeable batteries or power adapter.
- 24 months of warranty for the meter.
- The standard set includes the meter, conductivity cell, temperature sensor and a protective case.

TECHNICAL DATA

Function	Conductivity	Salinity	Temperature
Range	0 ÷ 1000.0 mS/cm, autorange - 6 subranges	NaCl 0 ÷ 296 g/l KCl 0 ÷ 239 g/l	-50.0 ÷ 200 °C***
Accuracy (± 1 digit)	±0.25 %* up to 19.99 mS/cm ±0.5%*above 20 mS/cm	±2.00%*	±0.1 °C**
Temperature compensation	-5 ÷ 70 °C		-
α coefficient	constant 2 %/°C		-
K constant	0.010 ÷ 20.000 cm ⁻¹		-
Power supply	2 x AA 1.2 V rechargeable battery, 5 V / 1000 mA power adapter		
Dimensions (mm)	L = 149; W = 82; H = 22		
Weight	245 g		

*The accuracy of the meter only.

**The accuracy of the meter only. The total error includes the meter's and probe's accuracy.

In the range 0 ÷ 100 °C the acceptable error of the probe with Pt-1000B resistor: ±0,8 °C., with Pt-1000A resistor ±0,35°C

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93