

pH/

/

CPC-511

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

LABORATORY pH / CONDUCTIVITY / SALINITY METER CPC-511

Easy in use laboratory measuring device, which measures pH, mV (redox potential), conductivity, salinity, TDS and temperature.

Characteristic features:

- Large LCD enables simultaneous readout of the measured function and temperature.
- Very easy in use.

In the pH measuring function:

- Calibration in 1 ÷ 3 points in buffer solutions.
- Automatic detection of the pH buffer solution's value 4.00, 7.00, 9.00 pH (optionally: 4.00, 7.00, 10.00 pH).
- Meter shows information about the pH electrode condition (readout of the buffer and slope values).
- Automatic temperature compensation.
- Depending on the chosen electrode, makes measurement in clean water, sewage, pastes, etc.

In the conductivity measuring function:

- Measures conductivity in distilled water and other liquids up to 1000 mS/cm.
- 5 sub ranges switched automatically (autorange).
- Salinity measurement converted to NaCl up to 250 g/l or KCl up to 200 g/l.
- Converts conductivity into salinity according to real characteristics and not a constant coefficient.
- Determines estimated value of the total dissolved solids (TDS).
- Calibration, by entering the K constant of the cell or by determining it with use of a standard solution.
- Possibility of entering the reference temperature value.
- Automatic temperature compensation.
- Constant α temperature coefficient: 2 % / °C. For precise measurements with temperature compensation it is recommended to use meters with variable coefficient (**CPC-502, CPC-505**).

Other features:

- Memory of 50 results.
- Wide temperature measuring range.
- Warranty for the meter: 24 months.

The set includes **CT2B-121** temperature probe with **Pt-1000B** resistor, accurate **ECF-1** conductivity cell and **EPS-1** pH electrode for measurements in clear water, which should not be used in other types of liquid. Measurements in liquid with sediment should be made with use of **IJ44A** pH electrode. Its unusual construction ("intermediate junction") protects the real junction (diaphragm) of the electrode against clogging, ensures stable measurements in these types of liquids or semi-liquid mass, in which other electrodes stop working quickly. When properly handled, the electrode's lifetime is longer than the standard electrodes



TECHNICAL DATA

Function	pH	mV	Conductivity / Salinity	Temperature
Range	-2.00 ÷ 16.00 pH	± 1999 mV	0 ÷ 1000 mS/cm (autorange) / up to 250 g/l NaCl up to 200 g/l KCl	-50.0 ÷ 199.9 °C
Accuracy (± 1 digit)	±0.01pH*	±1 mV*	±0,25%* / salinity: 2%*	±0.1 °C**
Temp. Compens. range	-5.0 ÷ 110.0 °C	-	-5.0 ÷ 70.0 °C	-
Input impedance	10 ¹² Ω	10 ¹² Ω	-	-
α coefficient	-	-	Constant: 2% / °C	-
K constant	-	-	0.010 ÷ 19.999 cm ⁻¹	-
Power	12 V / 100 mA power adapter			
Weight	520 g			
Dimensions (mm)	L = 200; W = 180; H = 20/50			

*The accuracy of the meter only.

**The accuracy of the meter only. The total error includes the meters and probe's accuracy.

In the range 0 ÷ 100 °C the acceptable error of the probe with Pt-1000B resistor: ±0.8 °C, with Pt-1000A resistor: ±0.35 °C.

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	